

MODEL	MAIN TANK (L)	ELEVATOR MAX LOAD (KG) (6 BAR)	PLATFORM LIFT	MAX STATIC LOAD** (KG)	ULTRASOUND POWER (KW)	HEATING POWER (KW)	MAIN TANK INTERNAL MEASURES (MM)	PLATFORM TRAY DIMMENSION (MM)	USEFUL HEIGHT (MM)	EXTERNAL MEASURES WITH TOP LID OPEN (MM)	OIL SEPARATOR LFS	AUTOMATIC TOP LID OPENING
ACM-100E	113	50	Pneumatic	100	1	3,75	600 x 400 x 470	550 x 290	310	1070 x 720 x 1360	YES	NO
ACM-200E	200	75	Pneumatic	150	2	7,5	800 x 500 x 500	750 x 370	300	1270 x 850 x 1520	YES	NO
ACM-350N	405	250	Pneumatic	470	3	11	1000 x 650 x 625	952 x 495	381	1807 x 1100 x 1735	YES	OPTIONAL
ACM-500N	587	350	Pneumatic	700	4	11	1200 x 670 x 730	1150 x 520	450	2010 x 1220 x 1810	YES	OPTIONAL
ACM-750N	840	500	Pneumatic	1 000	5	11	1400 x 800 x 750	1335 x 630	480	2270 x 1360 x 1890	YES	OPTIONAL
ACM-1000N	1 224	800	Pneumatic	1 600	7	15	1600 x 900 x 850	1550 x 725	556	2450 x 1490 x 2090	YES	YES
ACM-2000N	2 178	1 000	Hydraulic	2 000	9	23	1800 x 1100 x 1100	1666 x 915	754	2610 x 1830 x 2740	YES	YES
ACM-3000NW	3 279	1 000	Hydraulic	2 000	10	30	1700 x 1590 x 1215	1565 x 1340	850	2255 x 2180 x 3280	YES	YES
ACM-3000N	3 276	1 000	Hydraulic	2 000	12	30	2100 x 1300 x 1200	2000 x 1110	850	2750 x 1800 x 3000	YES	YES
ACM-4500N	5 190	1 800	Hydraulic	3 600	15	37,5	2400 x 1590 x 1360	2217 x 1251	900	3293 x 2306 x 3340	YES	YES
ACM-5500N	6 010	1 800	Hydraulic	5 000	18	45	2700 x 1590 x 1400	2600 x 1400	1 000	3543 x 2442 x 3660	YES	YES
ICM-8000N	9 184			8 000	27	60	3200 x 2050 x 1400		1 260	4100 x 2850 x 4350	YES	YES
ICM-12000N	13 258			12 000	36	75	4600 x 1950 x 1460		1 320	5920 x 2890 x 4335	YES	YES

*All ACM models available also in ICM execution, without the platform lift

**ICM model maximum load or ACM model with platform lift static on the lowest position

To get the best cleaning performance parts should be separated from each other and from the tank walls at least 100 mm.