



The most powerful Ultrasonic equipment at market

UltraTecno Valencia, SPAIN +34 961 666 565 - info@ultratecno.es www.ultratecno.eu



Main tank internal dimensions 1600 x 900 x 850 mm (1224 litres) Full stainless steel construction AISI 304/316L - 3 mm thickness - Height adjustable legs External Dimensions with Top Lid Open / Weight 2448 x 1492 x 2090 mm / 928 kg

Ultrasonic System Frequency **Ultrasonic Actual Power** Sweep Frequency Ultrasonic Emitters Sets Noise Reduction System

28 kHz 7000 W (7 sets) Synchronized Generators Digital ± 2% for smooth & safe cleaning 316L Flanged assembly at walls (replaceable) Patented ARF© <78db (A)

Elevator for agitation with platform lift

Pneumatic, max load 800 kg

Patented LFS© with Pump, Auxiliary tank & Automatic extraction **Oil Separation System** LFS[®] Recirculation pump

Stainless Steel EBARA CDX

Heating System 15 kW Ceramic Heaters into protective stainless-steel housing Acoustic & Thermal Insulation thickness Fire & Sound proof Stone rock 50 mm **Insulated Top Lid** Automatic (pneumatic) 30 mm thermal & acoustic insulation Safety water Level Sensor Electronic IFM LMT-102 (SS316-PEEK)

Inset Multilanguage 7" Color HMI Touch screen Manual & Automatic Preset Cycles Full process parameters customization Heating & US Programmable Timer / Preventive Maintenance Schedule Electrical Consumption Monitor / Detergent calculator / Hourly & starts counter

Optional Devices Available

Filtering / Automatic Water Refill / Hybrid Heating / Small parts basket / Steam Extraction / Automatic Top Lid Opening / Hands Free Operation Pedal





Construction

Green Label



Emission

Smart Interface



Best cost effective Cleaner